

TOWN OF CHESTER
203 Middlesex Avenue
Chester, Connecticut 06412



Office of the Building Official
Phone: 860-526-0013
Fax: 860-526-0004
BldgOfficial@chesterct.org

DATE _____

PERMIT # _____

SOLID FUEL STOVE PERMIT APPLICATION

This Permit Application is for the installation of NEW SOLID FUEL APPLIANCE only. Any and all Inspections and related approvals are null, and void should the appliance be Moved. Removed, Relocated and/or replaced.

ADDRESS SOLID FUEL APPLIANCE IS TO BE INSTALLED: _____

PROPERTY OWNER: _____

PROPERTY OWNER ADDRESS: _____

PHONE: _____ EMAIL ADDRESS: _____

INSTALLATION CONTRACTOR: _____ LICENSE #: _____

INSTALLER'S ADDRESS: _____ PHONE: _____

APPLIANCE MFG: _____ TYPE / STYLE: _____

LOCATION OF STOVE INSTALLATION: _____

PROPERTY OWNER'S SIGNATURE: _____

AS PART OF THE APPLICATION, PLEASE PROVIDE THE FOLLOWING:

- Copy of Connecticut Contractor's License.
- Insurance Certificate.
- Copy of mfg. Solid Fuel Stove Installation Instructions & Brochure of Appliance.

For Office Use Only:

PERMIT FEE: \$26.00 first thousand dollars of evaluation. \$16.00 for each \$1,000. thereafter
(State Educational Fees included)

TOTAL COST OF INSTALLATION \$ _____ TOTAL FEE: _____

Building Official: _____ Date of Approval: _____

Stove Installation Checklist

Before starting the first fire in your stove use this checklist to be sure that it is safely installed.

- ___1. The stove does not have broken parts or large cracks that make it unsafe to operate.
- ___2. A layer of sand or brick has been placed in the bottom of the firebox if suggested by the manufacturer.
- ___3. The stove is located on a non-combustible floor or an approved floor protection is placed under the stove.
- ___4. The stove is spaced at least 36 inches away from combustible material. If not, fire-resistant materials are used to protect woodwork and other combustible materials.
- ___5. Floor protection extends out 6 to 12 inches from the sides and back of the stove and 18 inches from the front where the wood is loaded.
- ___6. Stove pipe of 22 or 24 gauge metal is used.
- ___7. The stove pipe diameter is not reduced between the stove and the chimney flue.
- ___8. A damper is installed in the stove pipe near the stove unless one is built into the stove.
- ___9. The total length of stove pipe is less than 10 feet.
- ___10. There is at least 18 inches between the top of the stove pipe and the ceiling or other combustible material.
- ___11. The stove pipe slopes upward toward the chimney and enters the chimney higher than the outlet of the firebox.
- ___12. The stove pipe enters the chimney horizontally through a fire-clay thimble that is higher than the outlet of the stove firebox.
- ___13. The stove pipe does not extend into the chimney flue lining.
- ___14. The inside thimble diameter is the same size as the stove pipe for a snug fit.
- ___15. A double walled ventilated metal thimble is used where the stove pipe goes through the interior wall.

___16. The stove pipe does not pass through a floor, closet, concealed space or enter the chimney in the attic.

___17. A UL approved ALL FUEL metal chimney is used where a masonry chimney is not available or practical.

___18. The chimney is in good repair.

___19. The chimney flue is not blocked.

___20. The chimney flue lining and the stove pipe are clean.

___21. A metal container with tight fitting lid is available for ash disposal.

___22. The building official or fire inspector has approved the installation.

___23. The company insuring the building has been notified of the installation.